

位置情報については、おおよその位置を示したものとなります。

標	深	層	柱	土	色	孔内水位 / 測定月日	標準貫入試験					N	N 値 - 深度図
							深	10 cm ごと の打撃回数			打撃回数 / 貫入量		
								0	10	20			
尺	度	厚	図	質	調		度	10	20	30	値		
	0.60	0.60		埋土	暗灰褐	3.65 ≡	0.70	2 / 36			2 / 36	1.7	
1				粘土	暗褐 暗茶褐 暗褐		1.06					1.7	
							1.51	2 / 35			2 / 35	1.7	
2							1.86						
							2.46	2 / 33			2 / 33	1.8	
3								2.79					
								3.29	1 / 32		1 / 32	0.9	
4	3.70	3.10		シルト質粘土				3.61				0.9	
							4.15	1 / 33		1 / 33	0.9		
5							4.48						
						5.16	1 / 33		1 / 33	0.9			
6							5.49						
							6.19	1 / 32		1 / 32	0.9		
7	6.60	2.90		砂礫	暗灰		6.51				0.9		
	6.90	0.30		粘土	淡青灰		7.11	17 / 30		17 / 30	17		
	7.20	0.30		砂礫	黄灰緑		7.41	50 / 20		50 / 20	75		
8						8.01							
						8.65	50 / 21		50 / 21	71.4			
9						8.86							
						9.46	50 / 19		50 / 19	78.9			
10						9.65							
						10.32	50 / 18		50 / 18	83.3			
11						10.50							
						11.25	50 / 21		50 / 21	71.4			
12						11.46							
	12.10	4.90		細礫	暗緑灰		12.20	50 / 24		50 / 24	62.5		
						12.44							
13						13.19	50 / 20		50 / 20	75			
						13.39							
14						14.15	50 / 22		50 / 22	68.2			
						14.37							
15	15.36	3.26					15.16	50 / 20		50 / 20	75		
							15.36						