

位置情報については、おおよその位置を示したものとなります。

標	深	層	柱	土	色	孔内水位 / 測定月日	標準貫入試験					N	N値 - 深度図
							深	10 cmごとの打撃回数			打撃回数 / 貫入量		
								0	10	20			
尺	度	厚	状	質	調		度	10	20	30		値	
	0.70	0.70		表土	暗茶褐	3.50						0	
1							1.15	1 / 14		1 / 9	3 / 33	2.7	
2				ローム	茶褐		2.15	1	2	2	5 / 30	5	
3							2.45						
4	3.60	2.90					3.15				4 / 30	4	
5				凝灰質粘土	淡褐 茶褐		3.45	1	1	2	2 / 30	1.7	
6							4.15	1 / 20	1 / 15		2 / 35		
7	5.30	1.70					4.50						
8							5.15	1 / 12		2 / 8	5 / 30	5	
9							5.45						
10				シルト質粘土	暗灰		6.15	1 / 15		1 / 8	3 / 33	2.7	
11							6.48						
12	7.80	2.50					7.15	1 / 14	1 / 9	1 / 8	3 / 31	2.9	
13							7.46						
14				有機質粘土	暗茶灰		8.15	1 / 12		2 / 8	5 / 30	5	
15							8.45						
16	9.70	1.90					9.15	1 / 12	2 / 9	2 / 9	5 / 30	5	
17							9.45						
18	10.60	0.90		シルト	暗灰		10.15				16 / 30	16	
19							10.45	4	5	7			
20	11.50	0.90		砂礫	暗青灰		11.15				30 / 30	30	
21						11.45	9	10	11				
22				砂混りシルト	暗灰	12.15				37 / 30	37		
23	12.90	1.40				12.45	10	12	15				
24				有機質シルト	暗茶灰	13.15				9 / 30	9		
25						13.45	3	3	3				
26	14.50	1.60				14.15				7 / 30	7		
27						14.45	2	2	3				
28				シルト	暗灰	15.15				6 / 30	6		
29						15.45	2	2	2				
30	16.40	1.90				16.15				13 / 30	13		
31				砂礫	暗青灰	16.45							
32	17.60	1.20				17.15	50 / 9			50 / 9	167		
33						17.24							
34						18.15				17 / 30	17		
35				シルト	暗灰	18.45	5	6	6				
36						19.15				16 / 30	16		
37	19.90	2.30				19.45	5	5	6				
38						20.15				50 / 27	55.6		
39	20.70	0.80		細砂	暗青灰	20.42	13	16	7				
40						21.15				50 / 14	126		
41							46						

