

所在地 東京都新宿区新宿二丁目 1 5 - 2 7 付近

標	深	層	柱	土	色	孔内水位 / 測定月日	標準貫入試験					N
							深	10 cmごとの打撃数			打撃回数 / 貫入量	
								0	10	20		
尺	度	厚	状	質	調		度	10	20	30	値	
1				埋土	暗褐灰 / 黒灰	3.00	1.00	貫入不能			50 / 0	
2		2.80					2.00	1 / 20	1 / 15	2 / 35		
3				ローム	茶褐		3.00	1 / 20	1	2 / 30		
4		4.00				4.00	1 / 20	1 / 20	2 / 40			
5				粘土質ローム	黄茶褐		4.70	0.70				
6		5.50				5.00	1 / 43		1 / 43			
7				粘土	黄褐灰		6.00	1 / 20	1 / 30	2 / 50		
8		6.70				7.00	2 / 13	1 / 7	5 / 30			
9				凝灰質粘土	茶褐灰		7.40	0.70				
10		7.40				8.00	1	1	2 / 30			
11				粘土	茶褐灰		8.30			4 / 30		
12		9.70				9.00	1	2	2 / 30			
13				凝灰質粘土	暗緑灰		10.20	0.50		5 / 30		
14		10.20				10.30	2 / 15	1 / 5	8 / 30			
15				砂質粘土	暗緑灰		11.00			24 / 30		
16		12.00				11.30	6	8	10			
17				細砂	暗灰		12.00			32 / 30		
18		14.60				12.30	9	9	14			
19				粘土質細砂	暗灰		13.00	6	10	12 / 30		
20		19.10				13.30	4	6	8			
21				砂質粘土	暗灰		14.00	6	8	10 / 30		
22		21.00				15.00			18 / 30			
23				砂質粘土	暗灰		15.30	4	6	8		
24		22.00				16.00	5	7	8			
25				砂質粘土	暗灰		16.30			20 / 30		
26		23.00				17.00	6	6	8			
27				砂質粘土	暗灰		17.30			20 / 30		
28		24.00				18.00	6	7	8			
29				砂質粘土	暗灰		18.30			21 / 30		
30		25.00				19.00	8	10	12			
31				砂質粘土	暗灰		19.30			30 / 30		
32		26.00				20.00	8	8	10			
33				砂質粘土	暗灰		20.30			26 / 30		
34		27.00				21.00			24 / 30			

