

所在地 東京都新宿区神楽坂三丁目6付近

標 尺	深 度	層 厚	柱 状 図	土 質 区 分	色 調	孔 内 水 位 測 定 月 日	10cmごとの打撃回数				打撃回数 貫入量	N 値	標準貫入試験	
							深 度	0	10	20			N 値 ~ 深度図	
							度	10	20	30				
	0.90	0.90		表土	暗褐	4.80	1.15	1/15	1/5	1	3/30	3		
1							1.45							
2							2.15	1	1	2	4/30	4		
3				ローム	茶褐		3.15	1/15	1	1	3/35	2.6		
4							4.15				3/30	3		
5	4.80	3.90					4.45	1	1	1	3/30	3		
6				ローム質粘土	黄茶褐		5.15	1/15	1	1	3/35	2.6		
7							6.15	1	1	1	3/30	3		
8	7.50	2.70					7.15	1	2	2	5/30	5		
9				砂質粘土	暗茶灰		7.45							
10	8.40	0.90					8.15	1	3	4	8/30	8		
11							8.45	1	3	4	8/30	8		
12				細砂	暗黄灰		9.15				18/30	18		
13	12.45	4.05					9.45	5	5	8	30/30	30		
14	13.20	0.75		中砂	暗茶灰		10.15	6	7	7	20/30	20		
15							10.45							
16	15.10	1.90		細砂	暗灰		11.15	6	9	8	23/30	23		
17							11.45							
18	16.30	1.20		シルト混り細砂	暗灰		12.15	12	13	8	33/30	33		
19							12.45							
20	17.50	1.20		シルト	暗青灰		13.15	7	8	10	25/30	25		
21						13.45								
22				砂礫	暗緑灰	14.15	17	15	11	43/30	43			
23						14.45								
24						15.15				19/30	19			
25						15.45	4	5	10	30/30	30			
26						16.15				15/30	15			
27						16.45	5	6	4	30/30	30			
28						17.15				9/30	9			
29						17.45	2	3	4	30/30	30			
30						18.15		19/6		50/16	93.8			
31						18.31	31							
32						19.15		50/11		50/11	136			
33						19.26								
34						20.15		50/8		50/8	188			
35						20.23								
36						21.15		50/10		50/10	150			

