

所在地 東京都新宿区袋町10付近

標	深	層	柱	土	色	孔内水位 / 測定月日	標準貫入試験								
							深	10 cmごとの打撃回数			打撃回数 / 貫入量	N	N値 - 深度図		
								0	10	20					
尺	度	厚	状	質	調		度	10	20	30		値			
	0.40	0.40		埋土	暗褐	12/20 4.00						0			
	0.60	0.20		凝灰質粘土	暗茶褐										
1				ローム	茶褐	12/20 4.00	1.15				9 / 30	9			
							1.45	2	3	4					
2							2.15	2 / 15	3 / 13	5	10 / 38	7.9			
							2.53								
3							3.15	1 / 20	1 / 20		2 / 40	1.5			
							3.55								
4				凝灰質粘性土	暗茶褐	12/20 4.00	4.15	2 / 14	2	2	6 / 34	5.3			
	4.85	4.25					4.49								
5							5.15				5 / 30	5			
							5.45	1	1	3					
6							6.15				4 / 30	4			
	6.60	1.75					6.45	1	1	2					
7				砂混じり粘性土	黄茶褐	12/20 4.00	7.15				3 / 30	3			
							7.45	1	1	1					
8							8.15				3 / 30	3			
	8.60	2.00					8.45	1	1	1					
9				シルト混じり細砂	赤黄褐	12/20 4.00	9.15				21 / 30	21			
							9.45	6	7	8					
10							10.15				22 / 30	22			
	10.70	2.10					10.45	7	7	8					
11				シルト質細砂	黄褐	12/20 4.00	11.15				14 / 30	14			
							11.45	4	5	5					
12							12.15				17 / 30	17			
	11.90	1.20					12.45	5	6	6					
13				細砂	暗黄褐	12/20 4.00	13.15				20 / 30	20			
							13.45	6	7	7					
14							14.15				32 / 30	32			
							14.45	8	10	14					
15							15.15				18 / 9	50 / 29	51.7		
	16.90	5.00					15.44	15	17						
16				シルト混じり砂	暗灰	12/20 4.00	16.15				15 / 8	50 / 28	53.6		
							16.43	19	16						
17							17.15				19 / 30	19			
	17.80	0.90					17.45	6	6	7					
18							18.15				17 / 30	17			
							18.45	4	5	8					
19				シルト質粘性土	暗灰 淡灰 乳灰	12/20 4.00	19.15				15 / 30	15			

